


	<p align="center">Live Line Testers Model: LLT</p>
<p align="center">Edgcumbe</p>	

Introduction

The Live Line Tester Kits (LLT) have been specifically designed to perform measurements for both live voltage testing and phasing on overhead lines, in substations and within switchgear compartments. The kit includes all necessary components to effectively carry out these tests. All components are housed within a heavy duty carry case with secure compartments. Individual kits are available for system voltages of 3.3kV, 6.6kV, 11kV, 13.8kV and 33kV (50/60Hz). Made from high quality fibreglass rods and polycarbonate mouldings the equipment is suitable for both indoor and outdoor use – including wet conditions. The equipment has been designed to operate within the temperature range: - 25°C to + 50°C.

Designed to comply with the requirements of IEC1243 part 2, the LLT uses long established techniques for high voltage measurement. All readings are displayed on an analogue meter – the housing of which can be rotated through 240 degrees to ensure a perfect viewing position. A battery operated proving unit allows the equipment to be tested before and after measurements have been made and can also be used to check full scale deflection on the meter. Adaptors are available to allow Bowthorpe Rods to be connected for testing of raised conductors and a Repeater Station can be supplied to replicate meter readings at ground level. Space is reserved in the carry case for such accessories.

	<p>Each kit comprises the following ;</p> <ul style="list-style-type: none"> • Live line tester with earth lead • Phasing rod with phasing lead • 2 extension rods • 2 bend end adaptors • 2 overhead line adaptors • Proving Unit with batteries • Polymer Cleaning Kit • Instruction manual <p>Individual items can be supplied separately</p>
--	--

LLT 33kV Kit



Overhead Line Testing



Switchgear Testing



11kV Tester



11kV Phasing Rod



11kV Extension Rod



Proving Unit & Repeater Station



Bent End Adaptor

Length: 675mm
Weight: 0.27kg



Over Head Line Adaptors

Height: 100mm
Weight: 0.08kg



Bowthorpe Rod Adaptor

Length: 360mm
Weight: 0.62kg
Connection Cable: 12m

Tester	3.3kV	6.6kV	11kV	13.8kV	33kV
Resistor Chain	22.5MΩ	52.5MΩ	75MΩ	100mΩ	225MΩ
Measuring Range	5kV	10kV	15kV	20kV	40kV
Accuracy	±5% FSD			Movement	100uA TB
Length:	1025mm (3.3-13.8kV)				1200mm
Weight:	1.4kg (3.3-13.8kV)				2.3kg

Phasing Rod	Resistor Chain	as per Tester
Length:	1025mm (3.3-13.8kV)	1200mm
Weight:	1.4kg (3.3-13.8kV)	1.6kg

Extension Rod	Length: 907mm
Weight: 0.65kg	

Proving Unit	Voltage Output 3 to 5kV
Dimensions:	185 x 145 x 120 mm
Repeater Station	Used in conjunction with the Tester / Ph Rod
Dimensions:	185 x 145 x 120 mm

High Voltage Instruments Ltd policy is one of continuous development and hence we reserve the right to change specification / design without prior notice



High Voltage Instruments Ltd

1 Wellfield Court
Ibrox Business Park
Glasgow, G51 2JR
UK

Tel: +44(0)141 440 5800
Fax: +44(0)141 404 2561

web: www.hvil.co.uk

e-mail: sales@hvil.co.uk